

COMMANDER



ROTAX® ENGINE	600R E-TEC	900 ACE	900 ACE Turbo	COLOUR	Tactical Grey/Black
Engine details	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C.	Liquid-cooled, four-stroke D.O.H.C., turbocharged	DIMENSIONS	
Cylinders	2	3	3	Vehicle overall length*	3240 mm
Displacement	599.4 cc	899.0 cc	899.0 cc	Vehicle overall width	1200 mm
Bore	72,3 mm	74 mm	74 mm	Vehicle overall height	1500 mm
Stroke	73 mm	69.7 mm	69.7 mm	Ski stance	996 mm
Maximum engine speed	8100 RPM	7250 RPM	7750 RPM	Track nominal width	500 mm
Carburation	Electronic Direct Injection	EFI	EFI	Track nominal length	3923 mm
Recommended fuel type		Unleaded		Track profile height	44 mm 38 mm Cobra studded (spring only)
Minimum octane		95			
Fuel tank		42 liters			
Oil tank capacity (2-stroke)	3,4 liters	-	-		
POWERTRAIN				SUSPENSION	
Gearbox	2F/N/R with push-button reverse			Front suspension	LFS with bended lower A-Arms
Drive clutch type	pDrive with clickers (600R E-TEC) pDrive with slider shoes (900 ACE) pDrive (900 ACE Turbo)			Front shock	HPG 36
Driven clutch type	QRS			Rear suspension	EasyRide with adjustment
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder			Center shock	HPG 36
FEATURES				Rear shock	HPG 36
Frame	Radien-X		Heated throttle lever	Standard	
Skis	Blade DS+		Heated grips	Standard	
Seating	Modular, 1-up		Gauge	4.5-in. digital display	
Handlebar	U-type steel with hooks, low grab handle		Windshield	Extra high with side deflectors	
Riser block height	140 mm		Hitch	Standard	
Starter	Electric		Visor Plug front / rear	Front	
Reverse	RER (600R E-TEC) Electromechanical (ACE)		12V power outlet	Front	
			Air radiator with fan	Yes	
			LinQ attachment	Multi-LinQ plate	

* Vehicle overall length without snowflap.